

ALP 2.0

Passive Speaker



The AIMLINE ALP-passive column speakers are developed special for churches, conference-center and all public institutions, where a high speech intelligibility over a long distance is required.

The ALP 2.0 works as near field applications and under-balcony as well as for small conference rooms or huddle-rooms. Thanks to the same design it fits into any installations with Aimline ALP and ALM series.

Thanks to its controlled narrow vertical bandwidth the AIMLINE ALP-series is the right choice for acoustically difficult installation to avoid unwanted reflections.

The small and unobtrusive enclosure is a fit for most architecturally sensitive environments. The ALP-Series is available as 100-volt-version as well as low-impedance-version.

Aimline-ALP-speaker can be ordered in any RAL-colour to match the environment.

Wall-mounting-hardware included.

Aimline-Speakers are completely built in Europe.



ALP 2.0

Passive Speaker

Technical Data:

Configuration:	2 x 3,5" neodym-chassis
Power handling:	40 Watt 8 Ohm 100V: 40/20/10W
Dispersion horizontal:	90°
Dispersion vertical:	60°
Frequency-range:	100Hz – 18 kHz
Typical Throw:	10 m
Sensitivity:	90dB 1W/1m
Audio-Input:	Barrier-Strip
Enclosure:	Aluminium, powder-coated
Colour:	RAL 9016 all RAL-colours optional
Weight:	1,5kg
Dimensions:	H-269 x W-105 x D-111 (mm)