

**Dante™ 2 Channel Line Level Audio I/O**

Visionary's D200 Series interfaces allow you to quickly and easily add extra balanced inputs and outputs to your Dante™ audio network. Robust, professional POE devices require only Dante™ Controller software to deploy. Extruded chassis, Neutrik™ EtherCon and XLR connectors for high reliability.

**Features - D200L**

- ▶ 2 channels of balanced audio input to Dante™ networks  
2 XLR female
- ▶ Professional Line Levels
- ▶ Power Over Ethernet - POE  
1 RJ45
- ▶ Configure with Dante™ Controller - no other software required.  
2 input balanced line level Dante™ interface.

**Features - D250L**

- ▶ 2 channels of balanced audio output from Dante™ networks  
2 XLR male
- ▶ Professional Line Levels
- ▶ Power Over Ethernet - POE  
1 RJ45
- ▶ Configure with Dante™ Controller - no other software required.  
2 output balanced line level Dante™ interface.



## Dante™ 2 Channel Line Level Audio I/O

### Specifications

#### D200L

<b>Audio Input:</b>	Dante™ audio via Ethernet
<b>Audio Sampling:</b>	48kHz, 24 bits per sample
<b>Audio Levels:</b>	-18dBFS = +4dBu
<b>Maximum Level:</b>	+22dBu
<b>Input Type:</b>	Balanced Line Level
<b>Input Impedance:</b>	48K Ohm Differential, >1M Ohm 60Hz - 20KHz
<b>Frequency response:</b>	20 Hz to 20 kHz (± 0.1 dB)
<b>THD + N:</b>	< .007%
<b>Dynamic Range:</b>	100dBA
<b>SNR:</b>	100dBA
<b>Network Connector:</b>	RJ-45 Neutrik™ etherCon
<b>Input Connectors:</b>	Neutrik™ XLR
<b>Power Supply:</b>	PoE IEEE 802.3af Class 0
<b>Controls:</b>	Dante™ Controller Software
<b>LED Indicators:</b>	Power, Dante™, Status
<b>Construction:</b>	Extruded Aluminum Chassis
<b>Dimensions:</b>	82mm x 127mm x 47mm(WxDxH)
<b>Weight:</b>	0.2 kg
<b>Warranty:</b>	1 Year Parts and Labor

#### D250L

<b>Audio Output:</b>	Dante™ audio via Ethernet
<b>Audio Sampling:</b>	48kHz, 24 bits per sample
<b>Audio Levels:</b>	-18dBFS = +4dBu
<b>Headroom:</b>	>18dB above +4dBu
<b>Output Type:</b>	Balanced Line Level
<b>Output Impedance:</b>	100 Ohms
<b>Frequency response:</b>	20 Hz to 20 kHz (± 0.5 dB)
<b>THD + N:</b>	< 0.04%
<b>Idle Channel Noise:</b>	<-80dBu
<b>Crosstalk:</b>	<-85dB
<b>Network Connector:</b>	RJ-45 Neutrik™ etherCon
<b>Output Connectors:</b>	Neutrik™ XLR
<b>Power Supply:</b>	PoE IEEE 802.3af Class 0
<b>Controls:</b>	Dante™ Controller Software
<b>LED Indicators:</b>	Power, Dante™, Status
<b>Construction:</b>	Extruded Aluminum Chassis
<b>Dimensions:</b>	82mm x 127mm x 47mm(WxDxH)
<b>Weight:</b>	0.2 kg
<b>Warranty:</b>	1 Year Parts and Labor