

# System 10 camera-mount

## portable camera-mount digital wireless systems

With its compact, portable design, the **System 10 Camera-Mount** high-fidelity digital wireless system is ideally positioned to capture media on the go.

Perfect for video production, electronic news gathering (ENG) and every mobile application in between, the receiver features multiple mounting options to accommodate a variety of cameras and recording devices.

Like all of the products in the **System 10** wireless family, the **Camera Mount** provides three levels of diversity assurance: frequency, time and space. Instantaneous channel selection, sync and setup make the Camera-Mount extremely easy to use, while its digital 24-bit/48 kHz wireless operation provides the ultimate in sound quality and dependable performance. Also, as the receiver operates in the 2.4 GHz range, it remains completely free from TV interference at all times.

Available in handheld, lavalier and body-pack configurations, each **System 10 Camera-Mount** wireless system includes a camera shoe mount in addition to the receiver and transmitter.

- Digital 24-bit/48 kHz wireless operation for ultimate sound quality and dependable performance
- Operates in the 2.4 GHz range – completely free from TV interference
- Ultra compact receiver size with multiple mounting options
- Selectable balanced and unbalanced output jacks with level control for use with most cameras and recording devices
- Internal rechargeable 12-hr battery
- Separate headphone port and volume control for local audio monitoring
- Multi-pairing function to link a single receiver with up to eight body-pack or handheld transmitters
- Three levels of diversity assurance: frequency, time & space
- Automatic frequency selection for seamless, interference-free operation
- Extremely easy operation with instantaneous channel selection, sync and setup

### Recommended Retail Price:

**ATW-1701** – Body-Pack transmitter system €€  
**309,00€** (ex VAT) / **£257.50** (ex VAT)

ATW-R1700 receiver and ATW-T1001 UniPak® transmitter.  
 Select a Wireless Essentials® microphone or cable to complete the system.  
 EAN Code: 4961310127763

**ATW-1702** – Handheld Transmitter system €€  
**329,00€** (ex VAT) / **£274.00** (ex VAT)

ATW-R1700 receiver and ATW-T1002 handheld dynamic unidirectional microphone/transmitter. Includes AT8456a Quiet-Flex™ stand clamp.  
 EAN Code: 4961310127770

**ATW-1701/P** – Handheld Transmitter system €€  
**339,00€** (ex VAT) / **£282.50** (ex VAT)

ATW-R1700 receiver and ATW-T1001 UniPak® transmitter with ATR35cW omnidirectional lavalier microphone.



### Specifications\*:

#### OVERALL SYSTEM SPECIFICATIONS

<b>Operating Frequencies</b>	2.4 GHz ISM band
<b>Dynamic Range</b>	> 109 dB (A-weighted), typical
<b>Total Harmonic Distortion</b>	< 0.05% typical
<b>Operating Range</b>	30 m typical <i>Open range environment with no interfering signals</i>
<b>Operating Temperature Range</b>	0° C to +40° C <i>Battery performance may be reduced at very low temperatures</i>
<b>Frequency Response</b>	20 Hz to 20 kHz <i>Depending on microphone type</i>

\* Specifications are subject to change without notice.



#### RECEIVER SPECIFICATIONS

<b>Receiving System</b>	Diversity (frequency/time/space)
<b>Maximum Output Level</b>	3.5 mm (1/8"), TRS balanced: +6 dBV Dual mono, unbalanced: 0 dBV
<b>Power Supply</b>	100-240V AC (50/60 Hz) to 5V DC 0.5A switched mode external USB-type external power supply
<b>Battery</b>	Internal Battery: 3.7V rechargeable Li-ion battery
<b>Battery Life</b>	12 hours <i>Depending on environmental conditions</i> Battery Charging Time: 4 hours 30 minutes <i>Depending on environmental conditions</i> Charging Temperature Range: 5° C to +35° C
<b>Dimensions</b>	56,0 mm W x 91,4 mm H x 27,8 mm D
<b>Net Weight</b>	105 grams
<b>Accessories Included</b>	Two antennas; camera shoe mount; USB cable; AC adapter (USB-type); 3.5 mm (1/8") stereo cable

#### BODY-PACK TRANSMITTER SPECIFICATIONS

<b>RF Power Output</b>	10 mW
<b>Spurious Emissions</b>	Following federal and national regulations
<b>Input Connections</b>	Four-pin Locking Connector Pin 1: GND, Pin 2: INST INPUT, Pin 3: MIC INPUT, Pin 4: DC BIAS +9V
<b>Batteries</b>	Two 1.5V AA not included
<b>Battery Life</b>	>7 hours (alkaline) Depending on battery type and use pattern
<b>Dimensions</b>	70.2 mm W x 107.0 mm H x 24.9 mm D
<b>Net Weight</b>	100 grams ( <i>without batteries</i> )

#### HANDHELD TRANSMITTER SPECIFICATIONS

<b>RF Power Output</b>	10 mW
<b>Spurious Emissions</b>	Following federal and national regulations
<b>Batteries</b>	Two 1.5V AA not included
<b>Battery Life</b>	>7 hours (alkaline) Depending on battery type and use pattern
<b>Dimensions</b>	254.8 mm long, 50.0 mm diameter
<b>Net Weight</b>	280 grams ( <i>without batteries</i> )
<b>Accessory Included</b>	AT8456a Quiet-Flex™ stand clamp

\* Specifications are subject to change without notice.



**audio-technica**  
*always listening*

Audio-Technica Limited, Technica House, Unit 5, Millennium Way, Leeds LS11 5AL England  
 Audio-Technica SAS, 11 rue des Pyramides, 75001 Paris, France  
 Audio-Technica Niederlassung Deutschland, Lorenz-Schott-Str.5, D-55252 Mainz-Kastel, Germany  
 Audio-Technica Central Europe Ltd, Fogado u. 3, Budapest 1107, Hungary  
 ©2014 Audio-Technica, [www.audio-technica.com](http://www.audio-technica.com)