

## M-Vision 23000 WU

23,000 ISO / 20,500 ANSI Lumens | Contrast Ratio: 10,000:1 (Dynamic Black) | Part Number: 121-083

## M-VISION 23000 WU DIGITAL PROJECTOR

THE VISIONARIES CHOICE



23,000 ISO / 20,500 ANSI Lumens | Contrast Ratio: 10,000:1 (Dynamic Black) | Part Number: 121-083

### Colour System:

Blue + Red Laser and 4-segment colour wheel

### DMD Specification:

1920 x 1200 pixels native display.

Fast transit pixels for smooth greyscale and improved contrast.

### Display Type:

1 x 0.96" DarkChip™ DMD™

### Aspect Ratio:

16x10

### Fill Factor

87%

## Key Features

### Red Laser Assist

- Uses blue and red laser diodes for increased colour fidelity and highly accurate colours

### Video & Graphics Processing

- HDMI 1.4b for Side by Side, Frame Packing, Frame Sequential & TopBottom 3D Formats.
- Dual Flash Processing can be used to multiply the displayed frame rate for 3D sources.
- Dual Pipe Processing: Two sources in parallel for Left and Right eyes.
- Synchronisation of active glasses.
- 3G-SDI with loop-through.
- 24p and 1080p native display.

### Geometry Correction

- Cornerstone, Vertical & Horizontal Keystone, Pincushion & Barrel, and Image Rotation.
- Blanking control for custom input window sizing.

- Scaling for fixed aspect ratio screens.

## Edge Blending

- Correction for non-active pixels at the edge of the display.

## Picture in Picture

- Two sources can be displayed either one within the other (PIP) , or side by side, with the original aspect ratios maintained.

## HDBaseT® Interface

- Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows the projector to be placed up to 100m from source with low cost cabling.

## Colour Processing

- Powerful seven-point colour correction for accurate colour matching.

## Projector Controller Software

- Intuitive user interface for network control.
- Simultaneous control of user-defined groups of projectors.
- At-a-glance monitoring of projector status.

## Projector Automation

- Real-time clock provides daily on/off automation.

## Installation

- Integrated stacking mount pins.
- Eye bolts included for easy rigging.

## Source Compatibility:


3GSDI is SMPTE 292M, SMPTE 259M-C and SMPTE 424M compliant.

HDMI including Deep Color™ processing.

Graphics standards up to 1920 x 1200 resolution at 60Hz via HDMI or DisplayPort.

## Inputs/Outputs

Video & Computer			Communication & Control		
Type	Connector	Qty	Type	Connector	Qty
DisplayPort 1.1a	DisplayPort	2	3D Sync Out	BNC	1
HDMI 1.4b	HDMI	2	3D Sync In	BNC	1
3G-SDI in	BNC	1	LAN	RJ45	1

3G-SDI out	BNC	1	RS232	9-pin D-Sub	1
HDBaseT	LAN RJ45	1	Wired Remote	3.5mm Stereo Jack	1
			12V Trigger	3.5mm Stereo Jack	2
NOTE: The HDBaseT and LAN ports are not shared.					
3D Formats Supported			HDTV Formats Supported		
Frame Packing Dual Pipe Frame Sequential Side By Side (half) Top and Bottom			1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz), 1080i (50Hz, 60Hz), 720p (50Hz, 60Hz)		
Computer Compatibility			Bandwidth		
Up to 1920 x 1200			165 MHz on analog RGB 165 Megapixels per second on HDMI		
Remote Control			Automation Control		
Addressable IR Remote Control, wireless and wired On-Board keypad			Crestron RoomView® Connected PJLink Class 1 LAN RS232 AMX (Device Discovery) Served web page		
Colour Temperature			Operation		
3200K to 9300K					
Illumination Type			Typical Illumination Life		
Laser Light Source			20,000 hours		
Lenses					
Lens	Part No.	Optimised Focus Range*	Lens Shift		
0.9 - 1.2 : 1 zoom	120-624	0.92m - 13.46m	Vert: 0.45 (U) 0.45 (D) frame, Hor: 0.15 (L) 0.15 (R) frame		
1.20 - 1.56 : 1 zoom	120-625	1m - 17.5m	Vert: 0.5 (U) 0.5 (D) frame, Hor: 0.15 (L) 0.15 (R) frame		
1.50 - 2.00 : 1 zoom	120-626	2m - 21.8m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.15 (L) 0.15 (R) frame		
2.00 - 4.00 : 1 zoom	120-627	2.5m - 41.8m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.15 (L) 0.15 (R) frame		
4.00 - 7.00 : 1 zoom	120-628	4m - 42m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.15 (L) 0.15 (R) frame		
* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,					
Lens Mount					
Motorised shift, zoom and focus, with programmable shift					
Mechanical Mounting			Orientation		
Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet			Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes		
Power Requirements			Power Consumption		
110V~130Vac/ 50~60Hz 180V~240Vac/ 50~60Hz single phase * Note that in 120V operation, the projector will be at 65% brightness			Typical 1900W @ 240VAC in Normal mode Typical 1250W @ 110VAC in Normal mode		
Thermal Dissipation			Fan Noise		
Typical 6482 BTU/Hour @ 220VAC in Normal mode Typical 4265 BTU/Hour @ 110VAC in Normal mode			Normal mode: 50 dBA max, 48 dBA typical Eco mode: 48 dBA max, 46dBA typical		
Operating/Storage Temperature			Operating Humidity		
Operating: 0 to 35C (32 to 95F) Operating: >35 (95F) Projector automatically set to eco mode Storage: -20 to 60C (-4 to 140F)			10% to 90% relative, non-condensing		

## Weight (Chassis Only)

54 kg  
119 lb

## Dimensions

L: 74.8cm W: 53.0cm H: 24.8cm  
L: 29.5in W: 20.9in H: 9.8in

## Safety & EMC Regulations

UL / cUL, CB, CCC, FCC Class 1, CE, BIS, RoHS 2, IEC  
EN 60825-1 Class 3R Laser Product, IEC EN 62471-5 Risk  
Group 2

## Accessories

### Accessory

Infrared Remote (replacement)

### Part No.

117-780

*\*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.*

## Downloads

[PDF CAD Drawings](#)

[User Guides](#)

[AUTOCAD Drawings](#)

[Laser Risk Group Document](#)

[STEP / IGS Drawings](#)

[Important Information](#)

[Lens CAD Drawings](#)

[Control Protocol](#)



Certificate Number 13629  
ISO 9001

Specifications subject to change without notice. ©2020 Digital Projection.  
DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc



**DIGITAL PROJECTION, LTD** GREENSIDE WAY, MIDDLETON  
MANCHESTER, UK. M24 1XX  
T: +44.161.947.3300 | F: +44.161.684.7674 | [www.digitalprojection.co.uk](http://www.digitalprojection.co.uk)

**DIGITAL PROJECTION, INC** 55 CHASTAIN ROAD, SUITE 115 KENNESAW,  
GA. 30144  
T: 770.420.1350 } F: 770.420.1360 | [www.digitalprojection.com](http://www.digitalprojection.com)

**DIGITAL PROJECTION, CHINA** Rm A2301, Shaoyaoju 101 North Lane, Shi  
Ao International Center, Chaoyang District, Beijing 100029, PR China  
T: +86.10.58239771 | F: +86 10 58239770