

ALP 6.1

Passive Column-Speaker



The AIMLINE ALP- passive-column-speaker are developed special for churches, conference-center and all public institutions, where a high speech intelligibility over a long distance is required.

Thanks to its controlled narrow vertical bandwidth the AIMLINE ALP-series is the right choice for acoustically difficult installation to avoid unwanted reflections.

The small and unobtrusive enclosure is a fit for most architecturally sensitive environments.

The ALP-series is available as 100-volt-version as well as low-impedance-version.

Aimline-ALP-speaker can be ordered in any RAL-colour to match the environment.

Wall-mounting-hardware included.

Aimline-Speaker are completely built in Europe.

ALP 6.1

Passive Column-Speaker

Technical Data:

Configuration:	6 x 3,5" neodym-chassis 1 x HF-neodym
Power handling:	80 Watt 4ohm 100V: 60/30/15W
Dispersion horizontal:	120°
Dispersion vertical:	30°
Frequency-range:	90Hz – 20 kHz
Typical throw:	12 m
Sensitivity:	97dB 1W/1m
Audio-Input:	Barrier-Strip
Enclosure:	Aluminium, powder-coated
Colour:	RAL 9010 all RAL-colours optional
Weight:	5kg
Dimensions:	H-800 x W-105 x D-111 (mm)