



ATDM-1012

Digital SmartMixer



Features

- High-quality mic/line inputs with discrete amplifiers and remotely controllable mic preamps.
- Up to two ES954 Hanging Microphone Arrays (sold separately) can be integrated with the mixer.
- Full-matrix mixer with flexible input/output assignments.
- USB audio I/O (1 stereo input and 1 stereo output).
- Acoustic Echo Cancellation (AEC) and Noise Cancelling (NC) for use with up to 10 mic inputs.
- Audio-Technica LINK support for cascading up to 8 ATDM devices.
- Dante-compatible model (ATDM-1012DAN) available.
- 1U design is 19" rack compatible.

Specifications

Dynamic range / S/N ratio	110 dB or higher (A-weighted/ST) / 90 dB or higher (A-weighted/ST)
Maximum input level	MIC: -20 dBu LINE: +24 dBu ST: +20 dBV
Maximum output level	Output 1-8 (Balanced): +24 dBu / +20dBV / +10 dBV Output ST (Unbalanced): +20 dBV / +10 dBV / -13 dBV
Maximum gain	64 dB
Input/output terminal	MIC/LINE input 1-10: Euroblock 3 pin ST input 1/2: Euroblock 3 pin Output 1-8, ST output 1/2: Euroblock 3 pin
USB port	USB Type-B (Device): Stereo input x 1 ch, Stereo output x 1 ch (24-bit)
LINK/CHAIN	A/B/C/D terminal: RJ-45 x
Network port (ATDM-1012DAN only)	Network port: RJ-45 x 1 (Dante Primary/Secondary, Network port: RJ-45 x 2)
Power supply	100 to 240 V AC (50/60 Hz)
Operating temperature range	0 to 40°C (32 to 104° F)
Dimensions	482.6 mm (19") x 324.3 mm (12.77") x 44 mm (1.73") (W x D x H)
Weight	3.6 kg (7.9 lbs)
Accessories	<ul style="list-style-type: none"> • Power cable • Euroblock connector x 22

For product improvement, the product is subject to modification without notice.

