

PROFESSIONAL LOUDSPEAKERS
RF Series Installation Loudspeakers

Rigid and flexible loudspeakers for installation

RF6, RF10 & RFS12

AMC RF series installation loudspeakers and RFS12 subwoofer for high power and excellent sound delivery, designed for easy installation on walls or ceiling, as well as hanging or pole mounting. Rigid construction cabinets made of birch plywood with integrated hanging points and optional installation brackets for horizontal and vertical mounting. Universal horizontal and vertical bracket is also available.

RF6 & RF10 speakers feature two-way drivers and dual connectors for easy installations – speakON and Phoenix. RFS12 subwoofer features 12" low frequency driver. When used together with full range RF speakers it helps deliver more sound pressure with greater frequency response.



RF10



RF6



RFS12

Technical Specifications	RF6	RF10	RFS12
Type	Full range two-way loudspeaker	Full range two-way loudspeaker	Subwoofer
Impedance	8 Ω	8 Ω	8 Ω
Rated power	150 W RMS, 300 W peak	250 W RMS, 500 W peak	350 W RMS, 700 W peak
Sensitivity	97 dB 1W/1M	99 dB 1W/1M	96 dB 1W/1M
Maximum SPL	123 dB	128 dB	128 dB
Frequency response	75 Hz - 19 kHz (-5 dB)	60 Hz - 19 kHz (-5 dB)	33 - 160 Hz (-5 dB)
Driver dimensions	6.5" woofer, 1" tweeter	10" woofer, 1.35" tweeter	12" woofer
Crossover point	2.2 kHz	2 kHz	-
Dispersion	75° x 55°	75° x 55°	-
Dimensions (L x W x H)	290 x 270 x 480 mm	395 x 350 x 600 mm	591 x 485 x 535 mm
Weight	9 kg	18 kg	31.6 kg
Mounting options	Pole mounting, M10 rigging points, optional mounting brackets: RF H6B & RF H10B (horizontal), RF V6B & RF V10B (vertical), RF UB universal mounting bracket		M20 speaker pole attachment, M10 rigging points
Grill material	Steel, powder coated	Steel, powder coated	Steel, powder coated
Colour	Black	Black	Black